

Q-2 RGBW Color Flood Blind Strobe Light

Specifications	Optics	Light source	864 x RGBW SMD LEDs (5,700K)
		LEDs expected lifetime	50,000 hours*
		Lens options	110° fixed
	Photometric	Light output	12,000 lumen
		Efficacy	60 lm/W
	Features	Pan/Tilt	0° / 180°
		LED Panel	3 individual controllable segments
	Electrical	AC Power nominal	100 - 277V 50/60Hz
		AC Power max rating	90 - 305V 50/60Hz
		Maximum power consumption	275 W (all LEDs on)
		Typical power consumption	200 W (all LEDs on)
		Power factor	0.98 PF (230 V)
	Programming and Control	Protocol	USITT DMX512 A
		Setting and addressing	RDM Stand alone mode Oled graphical display / 4 buttons Software upgradable via Uploader cable (P/N:83062011)
		DMX channels	3, 6, 9, 12, 15 or 22
	Physical	Dimensions (L x H x W)	334 x 223 x 105 mm (13,2 x 8,8 x 4.1 in)
		Weight	6,0 kg (13,2 lbs.)
		Material	Aluminium
		Lens	Tempered glas front
		IP class	IP65
	Installation	Orientation	Any
		Rigging possibilities	Floor stand (included) or hanging (Omega Clamp included)
		Safety features	Bottom mount for Safety wire
	Thermal	Temperature range, Operating	-10° to +40°C (-14° to +104°F)
		Humidity (max.)	98%
		Cooling	Active, forced air, temperature-regulated, low noise
	Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 1m with bare ends
	Conforms to	2006/95/EC: Low Voltage Directive	EN 60598-1, EN 60598-2-17, EN 62471
		2004/108/EC: EMC Directive	EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3
		RoHS2 Directive	2011/65/EU
	Included Items	Included Items	Floor Stand (incl. screws) 1 pcs Omega bracket User manual Neopren pouch
	Fixtures and Accessories	Fixtures	Order no: 80030535 - Q-2 Color Flood Light
		Cables	Order no: 83062011 - SGM USB uploader cable
		Bracket	Order no: 83060602 - Omega bracket
		Barndoor	Order no: 83061128 - Accessory Holder Q-2 series Order no: 83061129 - Barndoor 4-way, P-2/Q-2 series Order no: 83061130 - Barndoor 8-way, P-2/Q-2 series Order no: 83061131 - Color frame, P-2/Q-2 series

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)